



SACO, DPS/MORRIS WAX

A Division of KWS Holdings LLC



441 DeGroate Rd., New Lenox, IL 60451

815-462-0939 Fax: 815-485-1194

www.dpswax.com email: info@dpswax.com

1601 Fairfax Traffic Way, Kansas City, KS 66115

500 N. National, Springfield, MO 65802

417-869-7333 Fax: 417-831-4671

www.morriswax.com

1284 Paraffin Wax

1284 is a specialty formulation of fully refined paraffin waxes used to make containers and votives.

PHYSICAL PROPERTIES

TEST METHODS	ASTM METHOD	SPECIFICATIONS		TYPICAL
		Minimum	Maximum	
Melt Point °F (°C)	D87	129 (53.9)	133 (56.1)	131 (55)
Kinematic Viscosity, cSt @210°F (98.9°C)	D445	3.0	4.5	3.5
Saybolt Viscosity, SUS @210°F (98.9°C)	D2161	36.2	39.5	37.8
Saybolt Color	D6045	+28	+30	+30
Odor	D1833	0	2.0	0
Needle Penetration, dmm @ 77°F (25°C)	D1321	9	16	12

FDA STATUS:

This product meets the FDA requirements set forth in 21 CFR 178.3710 for use in nonfood articles in contact with food and in 21 CFR 172.886 or use in food.