



441 DeGroate Rd., New Lenox, IL 60451  
 815-462-0939 Fax: 815-485-1194  
[www.dpswax.com](http://www.dpswax.com)  
 email: [info@dpswax.com](mailto:info@dpswax.com)

DPS/MORRIS WAX  
 A Division of Saco Petroleum

9807 Kaw Drive, Edwardsville, KS 66111  
 913-948-6220 Fax: 913-948-6242  
[www.sacopetroleum.com](http://www.sacopetroleum.com)



500 N. National, Springfield, MO 65804  
 417-869-7333 Fax: 417-831-4671  
[www.morriswax.com](http://www.morriswax.com)  
 email: [ghudson@morriswax.com](mailto:ghudson@morriswax.com)

## 1380 Paraffin Wax

**1380** is a fully refined paraffin wax derived from petroleum crude.

### PHYSICAL PROPERTIES

TEST METHODS	ASTM METHOD	SPECIFICATIONS		TYPICAL
		Minimum	Maximum	
Melt Point °F (°C)	D87	151 (66.1)	156 (68.9)	154 (67.8)
Kinematic Viscosity, cSt @210°F (98.9°C)	D445	----	----	6.4
Saybolt Viscosity, SUS @210°F (98.9°C)	D2161	----	----	47.2
Oil Content, Wt%	D721	----	0.8	0.3
Flash Point (C.O.C.), °F (°C)	D92	----	----	490 (254)
Saybolt Color	D6045	+26	----	+30
Needle Penetration, dmm @ 77°F (25°C)	D1321	----	----	17
Needle Penetration, dmm @ 100°F (37.8°C)	D1321	----	----	28

### FDA STATUS:

This product meets the FDA requirements set forth in 21 CFR 178.3710 for use in nonfood articles in contact with food and in 21 CFR 172.886 or use in food.