



441 DeGroat Road, New Lenox, IL 60451
(815) 462-0939 FAX: (815) 485-1194
<http://www.dpswax.com> email: skovac@dpswax.com

Micro Wax

Micro Wax is a white, laminating grade microcrystalline wax.

- Helps give a smooth appearance
- Eliminates wet spots
- Holds scent better
- Add 5% to 7%

PHYSICAL PROPERTIES

TEST METHODS	ASTM METHOD	SPECIFICATIONS		TYPICAL
		Minimum	Maximum	
Drop Melt Point °F (°C)	D127	170 (76.7)	180 (82.2)	175 (79.4)
Congealing Point °F (°C)	D938	---	---	165 (73.9)
Kinematic Viscosity, cSt @ 210°F (98.9°C)	D445	14.3	18.0	16.0
Saybolt Viscosity, SUS @ 210°F (98.9°C)	D2161	75.0	90.0	82.0
Flash Point (C.O.C.), °F (°C)	D92	530 (277)	---	---
Saybolt Color	D156	+16	---	---
Odor	D1833	---	---	0.0
Needle Penetration, dmm @ 77°F (25°C)	D1321	25	35	30

FDA STATUS:

This product meets the FDA requirements set forth in 21 CFR 178.3710 for use in non-food articles in contact with food and in 21 CFR 172.886 for use in food.