



441 DeGroate Rd., New Lenox, IL 60451  
815-462-0939 Fax: 815-485-1194  
[www.dpswax.com](http://www.dpswax.com)  
email: [info@dpswax.com](mailto:info@dpswax.com)

DPS/MORRIS WAX  
A Division of Saco Petroleum

9807 Kaw Drive, Edwardsville, KS 66111  
913-948-6220 Fax: 913-948-6242  
[www.sacopetroleum.com](http://www.sacopetroleum.com)



500 N. National, Springfield, MO 65804  
417-869-7333 Fax: 417-831-4671  
[www.morriswax.com](http://www.morriswax.com)  
email: [ghudson@morriswax.com](mailto:ghudson@morriswax.com)

## R2542 Fully Refined Paraffin Wax

**R2542** is a fully refined paraffin wax used to make pillars. It has a natural mottling look.

### PHYSICAL PROPERTIES

TEST METHODS	ASTM METHOD	SPECIFICATIONS		TYPICAL
		Minimum	Maximum	
Melt Point °F	D87	140	145	143
Oil Content (%)	D721	----	0.4	0.23
Color, Saybolt	D156	+30	----	+30
Needle Penetration, dmm @ 77°F	D1321	9	15	11
Needle Penetration, dmm @ 100°F	D1321	14	20	15

### FDA STATUS:

This product meets the FDA requirements set forth in 21 CFR: Sections 172.886 and 178.3710.