



---

## **1230 Paraffin Wax**

**1230** is a fully refined paraffin wax used for containers.

### **PHYSICAL PROPERTIES**

| <b>TEST METHODS</b>                     | <b>ASTM METHOD</b> | <b>SPECIFICATIONS</b> |                | <b>TYPICAL</b> |
|---|--------------------|-----------------------|----------------|----------------|
|   |                    | <b>Minimum</b>        | <b>Maximum</b> |                |
| Melt Point °F (°C)                      | D-87               | 129 (53.9)            | 136 (57.8)     | 132 (55.5)     |
| Kinematic Viscosity, cSt @212°F (100°C) | D-445              | 3.0                   | 4.2            | 3.7            |
| Oil Content, Wt%                        | D-721              | 0                     | 0.5            | ----           |
| Saybolt Color                           | D-6045             | 28                    | 30             | +30            |
| Odor                                    | D-1833             | 0                     | 1.0            | 0.5            |
| Needle Penetration, dmm @ 77°F (25°C)   | D-1321             | 10                    | 18             | 14             |

### **SHIPPED:**

10 lb. slabs in 60 lb. cartons or 2000 lb. covered gaylords

### **FDA STATUS:**

This product meets the FDA requirements set forth in 21 CFR 178.3710 for use in non-food articles in contact with food and in 21 CFR 172.886 for use in food.